






High Efficiency (Condensing)

	EZ SERIES PRO	NRCR PRO	EZ SERIES PRO	NRCR PRO	EZ SERIES PRO
EZ & NRCR					
Model Number	EZ111DV	NRCR111DV	EZ98DV	NRCR92DV	EZ71DV
GQ Reference Number	GQ-C3261WX-FF-US	GQ-C3261WXQ-FF US	GQ-C2861WX-FF US	GQ-C2661WXQ-FF US	GQ-C2661WX-FF US
Vent Type	Versatile Venting	Versatile Venting	Versatile Venting	Versatile Venting	Versatile Venting
SV Conversion	Yes	Yes	Yes	Yes	Yes
Dimensions (Inches)	26.1" x 18.1" x 11.8"	26.1" x 18.1" x 11.8"	26.1" x 18.1" x 11.8"	26.1" x 18.1" x 11.8"	26.1" x 18.1" x 11.8"
Weight (lbs)	60 lbs.	62 lbs.	60 lbs.	62 lbs.	60 lbs.
Min./Max. BTUh	12,800 - 199,900	12,800 - 199,900	12,800 - 180,000	12,800 - 165,000	12,800 - 160,000
UEF	0.98	0.98	0.98	0.98	0.98
Max. Hot Water Capacity	30°F Rise: 11.1 GPM		30°F Rise: 9.8 GPM	30°F Rise: 9.2 GPM	30°F Rise: 7.1 GPM
Water Inlet	3/4"				
Hot Water Outlet	3/4"				
Gas Inlet (1/2 in. capable)	3/4" (1/2 in. up to 40 ft.)		3/4" (1/2 in. up to 50 ft.)	3/4" (1/2 in. up to 60 ft.)	3/4" (1/2 in. up to 60 ft.)
Temp. Settings	100-140°F (In 5° intervals) (9 Options)	100-140°F (In 5° intervals) (9 Options)	100-140°F (In 5° intervals) (9 Options)	100-140°F (In 5° intervals) (9 Options)	100-140°F (In 5° intervals) (9 Options)
Default Temp. Option	120, 125, 130, 140°F				
Warranty	25 YEAR HEAT EXCHANGER, 5 year warranty on parts & 1 year reasonable labor	15 YEAR HEAT EXCHANGER, 5 year warranty on parts & 1 year reasonable labor	25 YEAR HEAT EXCHANGER, 5 year warranty on parts & 1 year reasonable labor	15 YEAR HEAT EXCHANGER, 5 year warranty on parts & 1 year reasonable labor	25 YEAR HEAT EXCHANGER, 5 year warranty on parts & 1 year reasonable labor
Hydrogen Compatible	Yes				
Ultra Low NOx	Yes				
Quick Connect	Yes				
Remote Included	No				
Min/Max Flow rate	0.4 GPM / 11.1 GPM	0.5 GPM / 11.1 GPM	0.4 GPM / 9.8 GPM	0.5 GPM / 9.2 GPM	0.4 GPM / 7.1 GPM
Wifi Compatible	Yes				
Bluetooth® Compatible	Yes				
High Altitude Approved	Up to 10,200 ft.				
Mobile Home Approved	Yes (OD or DV Install Only)				
PVC	2" or 3" or 4"				
Energy Star	Yes				
Pump Kit Compatible	Yes	No	Yes	No	Yes
Venting	2"/3"/4" PVC 2" Flex Pipe				

Vent Type

DV - Direct Vent
SV - Single Vent
DVC - Direct Vent Concentric
OD - Outdoor

Approvals

Residential



High Efficiency (Condensing)

	NRC							
Model Number	NRC111DV	NRC111OD	NRC98DV	NRC98OD	NRC711DV	NRC711OD	NRC661DV	NRC661OD
GQ Reference Number	GQ-C3257WX-FF US	GQ-C3257WX US	GQ-C2857WS-FF US	GQ-C2857WS US	N/A	N/A	N/A	N/A
Vent Type	DV	OD	DV	OD	DV	OD	DV	OD
SV Conversion	Yes	N/A	Yes	N/A	Yes	N/A	Yes	N/A
Dimensions (Inches)	24.2" x 18.3" x 9.4"	24.2" x 18.3" x 9.4"	24.2" x 18.3" x 9.4"	24.2" x 18.3" x 9.4"	23.6" x 13.8" x 6.7"	20.5" x 13.8" x 6.7"	23.6" x 13.8" x 6.7"	23.6" x 13.8" x 6.7"
Weight (lbs)	68 lbs.	66 lbs.	58 lbs.	57 lbs.	41 lbs.	40 lbs.	39 lbs.	36 lbs.
Min./Max. BTUh	16,000-199,900	16,000-199,900	16,000 - 180,000	16,000 - 180,000	15,000 - 157,000	15,000 - 157,000	15,000-120,000	15,000-120,000
UEF	0.91	0.91	0.91	0.92	0.89	0.89	0.89	0.89
Max. Hot Water Capacity	30°F Rise: 11.1 GPM		30°F Rise: 9.8 GPM	30°F Rise: 9.8 GPM	30°F Rise: 7.1 GPM	30°F Rise: 7.1 GPM	30°F Rise: 6.6 GPM	30°F Rise: 6.6 GPM
Water Inlet	3/4"							
Hot Water Outlet	3/4"							
Gas Inlet (1/2 in. capable)	3/4" (1/2 in. up to 40 ft.)		3/4" (1/2 in. up to 50ft)		3/4" (1/2 in. up to 70ft)		1/2" (1/2 in. up to 100 ft)	1/2" (1/2 in. up to 100 ft)
Temp. Settings	100-140°F (In 5° intervals)			115-140°F (In 5° Intervals)				
Default Temp. Option	120, 125, 130, 140°F				120, 130, 135, 140°F			
Warranty	12 year warranty on heat exchanger, 5 year warranty on parts & 1 year reasonable labor (Residential Installs)							
Ultra Low NOx	Yes							
Quick Connect	Yes				No			
Remote Included	Yes				Digital Display			
Min/Max Flow rate	0.5 GPM / 11.1 GPM		0.5 GPM / 9.8 GPM		0.5 GPM / 7.1 GPM	0.5 GPM / 7.1 GPM	0.5 GPM / 6.6 GPM	0.5 GPM / 6.6 GPM
Wifi Compatible	Yes							
High Altitude Approved	Up to 8,000 ft.							
Mobile Home Approved	Yes (OD or DV Install Only)							
PVC	3" or 4"	No	3" or 4"	No	3"	No	3"	No
Energy Star	Yes							
Pump Kit Compatible	Yes				No			
Venting	3" / 4" PVC Vent	N/A	3" / 4" PVC Vent	N/A	3" PVC Vent	N/A	3" PVC Vent	N/A