

High Efficiency Condensing



EZ & NRC



Model	EZ111DV	NRC111DV	NRC111OD	EZ98DV	NRC98DV
GQ Reference Number	GQ-C3259WX-FF US	GQ-C3257WX-FF US	GQ-C3257WX US	GQ-C2859WX-FF US	GQ-C2857WS-FF US
Vent Type	Versatile Venting	DV	OD	Versatile Venting	DV
SV Conversion	Yes	Yes	N/A	Yes	Yes
Dimensions (Inches)	27.0 x 18.5 x 12.8	24.2 x 18.3 x 9.4	24.2 x 18.3 x 9.4	27.0 x 18.5 x 12.8	24.2 x 18.3 x 9.4
Weight (lbs)	81 lbs.	66 lbs.	66 lbs.	81 lbs.	66 lbs.
Min./Max. Btuh	18,000 - 199,900	16,000-199,900	16,000-199,900	18,000 - 180,000	16,000 - 180,000
UEF	0.96	0.91	0.91	0.96	0.91
Max. Hot Water Capacity	35° F Rise: 11.1 GPM			35° F Rise: 9.8 GPM	35° F Rise: 9.8 gpm
Water Inlet	3/4"				
Hot Water Outlet	3/4"				
Gas Inlet (1/2 in. capable)	3/4" (1/2 in. up to 40 ft.)			3/4" (1/2 in. up to 50 ft.)	
Temp. Settings	100-140° F (In 5° intervals)			115-140° F (In 5° Intervals)	
Default Temp. Option	120, 125, 130, 140° F				
Warranty	25 Years Heat Exchanger, 5 year warranty on parts & 1 year reasonable labor	12-year warranty on heat exchanger, 5-year warranty on parts & 1-year reasonable labor (Residential Installs)		25 Years Heat Exchanger, 5 year warranty on parts & 1 year reasonable labor	12-year warranty on heat exchanger, 5-year warranty on parts & 1-year reasonable labor (Residential Installs)
Ultra Low NOx	Yes				
Quick Connect	Yes				
Remote Included	Yes				
Min/Max Flowrate	0.5 GPM / 11.1 GPM	0.5 GPM / 11.1 GPM	0.5 GPM / 11.1 GPM	0.5 GPM / 9.8 GPM	0.5 GPM / 9.8 GPM
Wireless Compatible	Yes				
High Altitude Approved	Up to 10,000 ft.	Up to 8,000 ft.	Up to 8,000 ft.	Up to 10,000 ft.	Up to 8,000 ft.
Mobile Home Approved	Yes (OD or DV Install Only)				
vv	2" or 3"	3" or 4"	No	2" or 3"	3" or 4"
Energy Star	Yes				
Pump Kit Compatible	Yes				

Vent Type
 DV - PVC, CPVC, PP Vent
 SV - Stainless Steel Vent
 DVC - Concentric, Stainless Steel Vent
 OD - Outdoor Vent

Versatile Venting
 See page 9-11



Model	NRC980D	NRC71DV	NRC71OD	NRC66DV	NRC660D
GQ Reference Number	GQ-C2857WS US	N/A	N/A	N/A	N/A
Vent Type	OD	DV	OD	DV	OD
SV Conversion	N/A	Yes	N/A	Yes	N/A
Dimensions (Inches)	24.2 x 18.3 x 9.4	23.6 x 13.8 x 6.7	20.5 x 13.8 x 6.7	23.6 x 13.8 x 6.7	20.5 x 13.8 x 6.7
Weight (lbs)	66 lbs.	41 lbs.	40 lbs.	39 lbs.	36 lbs.
Min./Max. Btuh	16,000 - 180,000	15,000 - 157,000	15,000 - 157,000	15,000-120,000	15,000-120,000
UEF	0.92	0.89	0.89	0.89	0.89
Max. Hot Water Capacity	35° F Rise: 9.8 gpm	35° F Rise: 7.1 gpm	35° F Rise: 7.1 gpm	35° F Rise: 6.6 gpm	35° F Rise: 6.6 gpm
Water Inlet	3/4"				
Hot Water Outlet	3/4"				
Gas Inlet (1/2 in. capable)	3/4" (1/2 in. up to 50ft)	3/4" (1/2 in. up to 70ft)	3/4" (1/2 in. up to 70ft)	1/2" (1/2 in. up to 100 ft)	1/2" (1/2 in. up to 100 ft)
Temp. Settings	115-140° F (In 5° Intervals)				
Default Temp. Option	120, 125, 130, 140° F	120, 130, 135, 140° F			
Warranty	12-year warranty on heat exchanger, 5-year warranty on parts & 1-year reasonable labor (Residential Installs)				
Ultra Low NOx	Yes				
Quick Connect	Yes	No	No	No	No
Remote Included	Yes	Digital Display			
Min/Max Flowrate	0.5 GPM / 9.8 GPM	0.5 GPM / 7.1 GPM	0.5 GPM / 7.1 GPM	0.5 GPM / 6.6 GPM	0.5 GPM / 6.6 GPM
Wireless Compatible	Yes				
High Altitude Approved	Up to 8,000 ft.				
Mobile Home Approved	Yes (OD or DV Install Only)				
PVC	No	3"	No	3"	No
Energy Star	Yes				
Pump Kit Compatible	Yes	No			

For technical support, contact us at
(866)766-7489

Visit us at
Support.Noritz.com